



Quality. Service. Value.

[Add this page to the Navigation view to display hyperlinks here]

[Add this page to the navigation structure to display a page banner here]



请使用翻译作用于这页底部以翻译页对汉语。

TPS Australia - Quality instruments since 1968.

WP-80 Waterproof pH-mV-Temperature Meter



[Full Size Image](#)

- ◆ **Rugged and Waterproof**
- ◆ **User-friendly**
- ◆ **Calendar Clock**
- ◆ **Good Laboratory Practices**
- ◆ **3600 Reading Notepad**
- ◆ **Automatic Datalogging**
- ◆ **RS232 Serial Port Interface**
- ◆ **Multiple Power Options**
- ◆ **Australian Made**

The WP series enclosure is fully waterproof to IP67 rating. The connectors are rated to IP65. The case, keypad and connectors are designed for maximum durability in the harshest conditions. The WP Series is equally at home in laboratory, field or industrial environments.

The 32 character alphanumeric display features a user-friendly menu system. This guides the user through every step of operation. Full text prompting and error messages are provided. Calibration and

Program the AutoLog function to automatically log readings into memory. Simply set the logging interval from 1 minute to 24 hours, start logging and walk away. The WP Series can log up to 3600 readings, along with the date and time.

The WP Series has RS232 serial port interface. All readings stored in memory and GLP information can be downloaded to a PC or printer. The RS232 serial port also allows the AutoLog function to log directly to a PC or printer

Messages are produced. Configuration and set-up are a breeze with the WP Series.

The Calendar Clock can be displayed continuously along with the data. The date and time are recorded with every reading, when using the Notepad and AutoLog functions.

To comply with Good Laboratory Practices (GLP) standards, the WP Series store the date, time and results of the last calibration. This information can be recalled when required. All readings stored in memory are stamped with the date and time.

To reduce errors when recording readings, the WP Series has a 3600 reading Notepad. At the touch of a button, readings can be recorded into memory, along with the date and time. This is especially useful when taking readings in wet environments.

WinTPS Windows software allows the WP Series to communicate with a PC for data download.

The WP Series is supplied with a rechargeable NiMH battery and charger as standard. Chargers for all countries are available. For extended field trips a solar panel, or a charger lead for a car cigarette lighter socket are also available.

The WP Series is proudly designed and manufactured in Australia. Our aim is to provide you with the best quality, service and value for money. The TPS Quality System has been certified in accordance with the AS/NZS ISO 9001 standard. Since 1968, TPS has built a reputation for excellent backup service that is second to none. Compare the list of features with the competition. The WP Series sets a new standard for handheld instruments.

Specifications

pH

Range : 0 to 14.00 pH
Resolution : 0.01 pH
Accuracy : +/-0.01pH

mV

Range : 0 to +/-500.0 &
0 to +/-1500 mV
(auto-ranging)
Resolution : 0.15 & 1 mV
Accuracy : +/-0.3 & +/-1 mV

Temperature

Range : -10.0 to 120.0 °C
Resolution : 0.1 °C
Accuracy : +/-0.2 °C

Input Impedance

Memory

3600 readings, including date and time.

Automatic Logging

User-set for one reading every 1 to 90 seconds, 1 to 90 minutes or 1 to 24 hours.

RS232 Serial Port Output

300, 1200 and 9600 Baud.
8 Bits, No Parity, 1 Stop Bit, XON/XOFF

Clock

24 Hour Calendar Clock

Battery Saver Function

On : Automatically switches

Input Impedance
 >3 x 10¹² Ohms

Asymmetry Range
 -1.00 to +1.00 pH

Slope Range
 85.0 to 105.0%

Temperature Compensation
 0 to 100 °C, automatic or manual. The WP-80 automatically detects whether or not the temperature sensor is connected.

Automatic Buffer Recognition
 4.01, 6.86, 7.00, 9.18 and 10.01 pH

Enclosure
 Tough, anti-static Luran-S plastic case, waterproof to IP67. Connectors waterproof to IP65. The instrument will float if dropped into water.

Display
 32 Character alphanumeric LCD with user-friendly menu system and full-text messages.

off after 5 minutes of no use.
 Off : Unit remains on for continuous use.

Good Laboratory Practices
 Date, time and results of last successful calibration are stored, and can be recalled when required. GLP information can be printed or downloaded to PC with the RS232 serial port interface. Warning of failed calibration is provided.

Power
 6V NiMH Rechargeable battery pack for approx 75 hours operation. Battery charger for country of choice supplied. Battery can be charged from any 12V DC source.

Dimensions
 187 x 110 x 51 mm

Mass
 Instrument : Approx 440g
 Full Kit : Approx 1.7kg

Environment
 Temperature : 0 to 45 °C
 Humidity : 0 to 95% R.H.

Ordering Information

	Part No
WP-80 pH-mV-Temp 1m.....	121109/1
WP-80 pH-mV-Temp 3m.....	121109/3
WP-80 pH-mV-Temp 5m.....	121109/5

1, 3 & 5 metre Options Include

1 metre bundle 121109/1:

pH Sensor, 1m Surface only....	121207
Temperature Sensor, 1m.....	121247
pH7.00 Buffer, 200mL.....	121387
pH4.01 Buffer, 200mL.....	121381
Battery Charger.....	130037
Manual.....	130050

3 metre bundle 121109/3:

pH Sensor, 3m Submersible....	111231
Temperature Sensor, 3m.....	121255
pH7.00 Buffer, 200mL.....	121387
pH4.01 Buffer, 200mL.....	121381
Battery Charger.....	130037
Manual.....	130050

Part No

Options and Accessories

pH Sensor Upgrade: difficult samples such as meat, dairy, slurries...

pH, Intermediate Junc, 1m.....	121200/1
pH, Intermediate Junc, 3m.....	121200/3
pH, Intermediate Junc, 5m.....	121200/5

ORP Sensors:

ORP, Surface only, 1m.....	121262
ORP, Intermediate Junc, 1m.....	121269
ORP Calibration Solution.....	121309

Cable Extension:

Extra cable, per metre.....	130040
-----------------------------	--------

Computer Interface:

Serial cable for computer.....	130041
Serial to USB adaptor cable.....	130087
WinTPS Software for Windows.....	130086

5 metre bundle 121109/5:

pH Sensor, 5m Surface only....	111224
Temperature Sensor, 5m.....	121256
pH7.00 Buffer, 200mL.....	121387
pH4.01 Buffer, 200mL.....	121381
Battery Charger.....	130037
Manual.....	130050

Power options:

12V Solar Panel.....	130012
12V Car Cigarette lighter lead...	130046
12V Clip lead, separate battery..	130052

Carry case:

Aluminium Carry Case.....	130059
---------------------------	--------

Please click the following links for further details on the TPS range of sensors...

[pH Sensors](#)

[Redox \(ORP\) Sensors](#)

 [Download this Specification Sheet in PDF format.](#)

 [Download the full colour WP Series Brochure \(832KB PDF\).](#)

 [Download the manual for this instrument.](#)

Hint : Right click on a link, then select "Save Target As..." or "Save Link As..." to save the file to your own computer.

If you do not have Adobe Acrobat in your computer, a free Acrobat Reader can be downloaded by clicking on the following link.



TPS reserves the right to change any part of this specification without notice.

Version 2.0

Copyright © 2002 T.P.S. Pty Ltd

[Add this page to the Navigation view to display hyperlinks here]

<p>Web Author : TPS Pty Ltd Copyright © 2002-2010 T.P.S. Pty Ltd A.B.N. 30 009 773 371 Last modified: September 14, 2011</p>	
---	--