Model	Specification			
Optical Specification         3300         3700         3500           Brightness         3300         3700         3500           Display Technology         3LCD(HLD)           Contract Ratio         100,000:1         WXGA (1280x800)         WUXGA (1920 X 1200)           Light Source         (HLD 203+) + P2W         Ught Source Time         30,000H         Aspect Ratio         4:3(Standard) / 16:9 (Compatible)         16:10(Standard) / 4:3 (Compatible) <td< th=""><th>Short Throw Projector</th><th></th><th></th><th></th></td<>	Short Throw Projector			
Optical Specification         3300         3700         3500           Brightness         3300         3700         3500           Display Technology         3LCD(HLD)           Contract Ratio         100,000:1         Resolution           Resolution         XGA (1024x768)         WXGA (1280x800)         WUXGA (1920 X 1200)           Light Source         (HLD 203+) + P2W         Ught Source Time         30,000H           Aspect Ratio         4:3(Standard) / 16:9 (Compatible)         16:10(Standard) / 4:3 (Compatible)         16:10(Standard) / 4:3 (Compatible)           Projection Lens         Manual         Focus         Introduction of the part o	Model	AEX335ST	AEW375ST	AEU355ST
Display Technology	Optical Specification			
Contract Ratio   100,000:1	Brightness	3300	3700	3500
Contract Ratio   100,000:1	Display Technology		3LCD(HLD)	
Light Source Time Aspect Ratio	Contract Ratio			
Light Source Time	Resolution	XGA (1024x768)	WXGA (1280x800)	WUXGA (1920 X 1200)
Aspect Ratio   4:3(Standard) / 16:9 (Compatible)   16:10(Standard) / 4:3 (Compatible)   16:10(Standard) / 5:10(Standard)   16:10(Standard) / 5:10(Standard)   16:10(Standard) / 5:10(Standard) / 5:10(Standard)   16:10(Standard) / 5:10(Standard)   16:10(Standard) / 16:1	Light Source		(HLD 203+ ) + P2W	
Projection Lens         Manual           Focus         Manual           Throw Ratio         0.46 : 1 (80"@0.75m)         0.46 : 1 (80"@0.71m)           F         F:1.8         f=6.08mm           Screen Size         0.455m ~ 0.943m (50"~100")         0.429~0.89m (50"~100")           Generic Specification           Speaker         1*16W           Scranning Frequency         Hsync Frequency 15~91KHz / Vsync Frequency 24~85Hz           Computer Signal Input         PC, VGA, SVGA, XGA, SXGA,WXGA,UXGA,WUXGA, Muxor           Video Compatibility         PAL, SECAM, NTSC 4.43, PAL-M, PAL-N, 480i, 480p, 576i, 576p, 720p, 1080p and 1080i           Power Consumption         420W         490W           ECO Standby Mode         <0.5W	Light Source Time		30,000H	
Throw Ratio	Aspect Ratio	4:3(Standard) / 16:9 (Compatible)	16:10(Standard) / 4:3 (Compatible)	16:10(Standard) / 4:3 (Compatible)
Throw Ratio	Projection Lens			
F:1.8	Focus		Manual	
Fe6.08mm   Screen Size	Throw Ratio	0.46: 1 (80"@0.75m)	0.46 : 1 (8	0"@0.71m)
Screen Size	F		F:1.8	
Generic Specification         1*16W           Scranning Frequency         Hsync Frequency 15~91kTz / Vsync Frequency 24~85Hz           Computer Signal Input         PC, VGA, SVGA, XGA, SXGA,WXGA,UXGA,WUXGA, Mac           Video Compatibility         PAL, SECAM, NTSC 4.43, PAL-M, PAL-N, 480i, 480p, 576i, 576p, 720p, 1080p and 1080i           Power Consumption         420W           ECO Standby Mode         < 25 Standby Mode           Network standby         V: ±15°(auto+manual), H: ±15°(manual), H: ±10°(manual), Corner Keystone           V: ±10°(auto+manual), H: ±10°(manual), Pincushion/Barrel Correction, Corner Keystone         V: ±10°(auto+manual), H: ±10°(manual), Corner Keystone           OSD(Languages)         26 languages: English, German, French, Italian, Spanish, Polish, Swedish, Dutch, Portugese, Japanese, Simplified Chinese, Traditional Chinese, Korea, Russian, Arabic, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech, Kazak, Vietnamese, Thai, Farsi           Input Terminals         VGA x2; Audio in(mini jack 3.5mm)x1; Video x1 Audio in(L/R)RCAx2; HDMI x2; USB-Ax1, USB-Bx1(Display), RJ45x1(Display)           Output Terminals         VGA x1, Audio out (mini-jack, 3.5mm) x1           Other Terminals         VGA x1, Audio out (mini-jack, 3.5mm) x1           Other Terminals         RS-232x1, RJ45 x1(for control), USB-Bx1(f	f		f=6.08mm	
Speaker	Screen Size	0.455m ~ 0.943m (50"~100")		(50"~100")
Scranning Frequency	Generic Specification			
Computer Signal Input         PC, VGA, SVGA, XGA, SXGA,WXGA,UXGA,WUXGA, Mac           Video Compatibility         PAL, SECAM, NTSC 4.43, PAL-M, PAL-N, 480i, 480p, 576i, 576p, 720p, 1080p and 1080i           Power Consumption         420W           ECO Standby Mode         490W           Network standby         <2W	Speaker			
Video Compatibility         PAL, SECAM, NTSC 4.43, PAL-M, PAL-N, 480i, 480p, 576i, 576p, 720p, 1080p and 1080i           Power Consumption         420W         490W           ECO Standby Mode         <0.5W	Scranning Frequency			
Power Consumption 420W 490W  ECO Standby Mode	Computer Signal Input			
ECO Standby Mode  Network standby  Cy: ±15°(auto+manual), H: ±15°(manual), Pincushion/Barrel Correction, Corner Keystone  26 languages: English, German, French, Italian, Spanish, Polish, Swedish, Dutch ,Portugese, Japanese, Simplified Chinese, Traditional Chinese, Korea, Russian, Arabic, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech, Kazak,Vietnamese,Thai, Farsi  NGA x2; Audio in(mini jack 3.5mm)x1; Video x1 Audio in(L/R)RCAx2; HDMI x2; USB-Ax1, USB-Bx1(Display), RJ45x1(Display)  Output Terminals  VGA x1, Audio out (mini-jack,3.5mm) x1  Other Terminals  RS-232x1, RJ45 x1(for control), USB-Bx1(for up-grade)  Mechanical Specification  Power Requirement  AC 100 – 240 V ~ 50-60 Hz  Net. Weight(KG)  5.5kg  Max Dimensions  Accessories		PAL, SECAM, NTSC 4.43	3, PAL-M, PAL-N, 480i, 480p, 576i, 576	p, 720p, 1080p and 1080i
Network standby<2WKeystone CorrectionV: ±15°(auto+manual), H: ±15°(manual), Pincushion/Barrel Correction, Corner KeystoneV: ±10°(auto+manual), H: ±10°(manual), H: ±10°(manual), Corner KeystoneOSD(Languages)26 languages: English, German, French, Italian, Spanish, Polish, Swedish, Dutch ,Portugese, Japanese, Simplified Chinese, Traditional Chinese, Korea, Russian, Arabic, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech, Kazak,Vietnamese, Thai, FarsiInput TerminalsVGA x2; Audio in(mini jack 3.5mm)x1; Video x1 Audio in(L/R)RCAx2; HDMI x2; USB-Ax1, USB-Bx1(Display), RJ45x1(Display)Output TerminalsVGA x1, Audio out (mini-jack,3.5mm) x1Other TerminalsRS-232x1, RJ45 x1(for control), USB-Bx1(for up-grade)Mechanical SpecificationAC 100 – 240 V ~ 50-60 HzNet. Weight(KG)5.5kgMax Dimensions365(W) x 365(D) x 140(H) mmAccessories		420W		WC
Keystone CorrectionV: ±15°(auto+manual), H: ±15°(manual), Pincushion/Barrel Correction, Corner KeystoneV: ±10°(auto+manual), H: ±10°(manual), Corner KeystoneOSD(Languages)26 languages: English, German, French, Italian, Spanish, Polish, Swedish, Dutch, Portugese, Japanese, Simplified Chinese, Traditional Chinese, Korea, Russian, Arabic, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech, Kazak, Vietnamese, Thai, FarsiInput TerminalsVGA x2; Audio in(mini jack 3.5mm)x1; Video x1 Audio in(L/R)RCAx2; HDMI x2; USB-Ax1, USB-Bx1(Display), RJ45x1(Display)Output TerminalsVGA x1, Audio out (mini-jack, 3.5mm) x1Other TerminalsRS-232x1, RJ45 x1(for control), USB-Bx1(for up-grade)Mechanical SpecificationAC 100 – 240 V ~ 50-60 HzNet. Weight(KG)5.5kgMax Dimensions365(W) x 365(D) x 140(H) mm				
Keystone Correction  V: ±15 (auto+manual), H: ±16 (manual), Pincushion/Barrel Correction, Corner Keystone  26 languages: English, German, French, Italian, Spanish, Polish, Swedish, Dutch, Portugese, Japanese, Simplified Chinese, Traditional Chinese, Korea, Russian, Arabic, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech, Kazak, Vietnamese, Thai, Farsi  Input Terminals  VGA x2; Audio in(mini jack 3.5mm)x1; Video x1 Audio in(L/R)RCAx2; HDMI x2; USB-Ax1, USB-Bx1(Display), RJ45x1(Display)  Output Terminals  VGA x1, Audio out (mini-jack, 3.5mm) x1  Other Terminals  RS-232x1, RJ45 x1(for control), USB-Bx1(for up-grade)  Mechanical Specification  Power Requirement  AC 100 – 240 V ~ 50-60 Hz  Net. Weight(KG)  5.5kg  Max Dimensions  Accessories	Network standby		<2W	
OSD(Languages) Chinese, Traditional Chinese, Korea, Russian, Arabic, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech, Kazak, Vietnamese, Thai, Farsi  VGA x2; Audio in(mini jack 3.5mm)x1; Video x1 Audio in(L/R)RCAx2; HDMI x2; USB-Ax1, USB-Bx1(Display), RJ45x1(Display)  Output Terminals  VGA x1, Audio out (mini-jack, 3.5mm) x1  Other Terminals  RS-232x1, RJ45 x1(for control), USB-Bx1(for up-grade)  Mechanical Specification  Power Requirement  AC 100 – 240 V ~ 50-60 Hz  Net. Weight(KG)  5.5kg  Max Dimensions  365(W) x 365(D) x 140(H) mm  Accessories	Keystone Correction			H: ±10°(manual),
Mechanical Specification         AC 100 − 240 V ~ 50-60 Hz           Net. Weight(KG)         5.5kg           Max Dimensions         365(W) x 365(D) x 140(H) mm	OSD(Languages)	26 languages: English, German, French, Italian, Spanish, Polish, Swedish, Dutch ,Portugese, Japanese, Simplified Chinese, Traditional Chinese, Korea, Russian, Arabic, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian,		
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Input Terminals	RJ45x1(Display)		
Mechanical Specification           Power Requirement         AC 100 − 240 V ~ 50-60 Hz           Net. Weight(KG)         5.5kg           Max Dimensions         365(W) x 365(D) x 140(H) mm           Accessories	Output Terminals			
Power Requirement $AC\ 100-240\ V\sim 50\text{-}60\ Hz$ Net. Weight(KG) $5.5\text{kg}$ Max Dimensions $365(W)\ x\ 365(D)\ x\ 140(H)\ mm$ Accessories		RS-232x1, RJ45 x1(for control), USB-Bx1(for up-grade)		
Net. Weight(KG)         5.5kg           Max Dimensions         365(W) x 365(D) x 140(H) mm           Accessories				
Max Dimensions         365(W) x 365(D) x 140(H) mm           Accessories	Power Requirement	AC 100 − 240 V ~ 50-60 Hz		
Accessories	Net. Weight(KG)	5.5kg		
	Max Dimensions	365(W) x 365(D) x 140(H) mm		
Standard Power cord, VGA cable, Remote control, Service Card, QSG(for Projector)	Accessories			
	Standard	Power cord, VGA	cable, Remote control, Service Card, C	SG(for Projector)

Projection Distance \*All measurements are approximate and may vary from the actual sizes.

\*specifications subject to change without notice.

## AEX335ST

AEX335ST			unit : m
Screen Size	4:3	16:10	16:9
(inch)	Distance	Distance	Distance
50	0.455	0.484	0.498
60	0.552	0.587	0.605
70	0.650	0.692	0.711
80	0.748	0.796	0.817
90	0.845	0.900	0.924
100	0.943	1.004	1.030


70	0.030	0.092	0.7 11	70
80	0.748	0.796	0.817	80
90	0.845	0.900	0.924	90
100	0.943	1.004	1.030	100
AEU355ST			unit : m	<u>.</u>
Screen Size	4:3	16:10	16:9	
(inch)	Distance	Distance	Distance	

AEU355ST			unit : m
Screen Size	4:3	16:10	16:9
(inch)	Distance	Distance	Distance
50	0.486	0.429	0.441
60	0.590	0.521	0.535
70	0.694	0.613	0.630
80	0.799	0.706	0.725
90	0.902	0.797	0.819
100	1.007	0.890	0.914

AEW375ST			unit : m
Screen Size	4:3	16:10	16:9
(inch)	Distance	Distance	Distance
50	0.486	0.429	0.441
60	0.590	0.521	0.535
70	0.694	0.613	0.630
80	0.799	0.706	0.725
90	0.902	0.797	0.819
100	1.007	0.890	0.914

Dealer





# **AE-ST Series**

New generation HLD (High Lumen Density) LED light source shows the clear, bright, true color image under easy setup features and provide 30,000 hours light source life time to reduce the maintenance cost.

- Powerful correction function
- 3LCD color balance
- 360 ° projection technongy
- Up to 30,000 hrs lamp life time
- Available display via USB or RJ45 cable
- Plentiful and practical projector display modes








#### > HLD LED Light Source / Brightness: 3300lm ~ 3700lm

The projector with new generation light source, HLD(High Lumen Density) LED ColorSpark, provide the real color of LED light source. Show a clear, bright, natural images to you during the business presentation. Provide the users a particularly prominent experience.



#### **♦** 30,000 hours lamp life time, allowing the customer user-friendly feeling.


HLD LCD light source provide 30,000 hours lamp life. it don't need replace the lamp up to 10 years. it's reduce the consumable and maintenance. The Lamp without Hg and environmentally friendly for earth.



#### **♦** Short Throw Distance

Short Throw Projector make a shorter distance for installtion. Avoid the light to the eye straight. Throw Ratio:


80" @ 75cm(XGA) / 71cm(WXGA, WUXGA).



### Logo capture function in start screen.


By means of OSD menu selection, users can set their own business or personal images as a start logo. In the external demo companies or individuals can show their unique image, breaking the stereotyped image of the default start logo.





## **≯** Plentiful interface, more expanded display interface: RJ45 & USB.

Not only the mainstream interface but also LAN & USB terminals can project any kind of signals. USB slot can support data reading such as jpeg or pdf\*\*.



<sup>\*</sup> USB-A slot has limit with files, please make sure that the file can be read or not before use.

#### Equipped with 16W speaker


Build in 16W speaker make the picture and sound show with same equipment. Reduce other installation for sound.






#### Powerful correction function.

Having the convenient manual and automatic Vertical correction, and manual Horizontal correction function. Moreover, user can use Corner Keystone, Pincushion/Barrel Correction\* to adjust the projected picture. Ensure user can project in any uneven surface. \*This function doesn't support by AEU355ST.




#### Multi-projection way: support 360° projection in vertical.

The projector supports the following project ways: Front, Rear, Ceiling / Front, Ceiling / Rear, Auto ceiling / Front, Auto ceiling / Rear and support  $360^{\circ}$  projection.



## Rigid dustproof design.

High efficiency ESD filter can effectively extend the projector life to ensure the image quality. Projector built-in auto-detected system, always checks the projector's air volume, and automatically detects whether the filter is blocked. It can actively give the alarm to clean up the filter message to protect the machine and improve the service life.



Quick-release Filter Mak it easy to installed



## **♦** Select color modes by customer demand.

Dynamic, standard, cinema, blackboard, colorboard or you can deside by yourself, whether in bright or blackboard, white wall environment can be adjusted to the most suitable screen color performances to enjoy the real wonderful screen.

## Double password lock and anti-theft function.

User's power-on password protection and keyboard or remote control lock function can avoid the projector error operation and theft. In addition, the projector is equipped with Kensington anti-theft lock slot abd prevent the projector being stolen.

<sup>\*\*</sup>WUXGA model doesn't support PDF files with USB-A slot.