# HP Latex 630 Printer



## Embrace new possibilities with outstanding quality—easily



## POSSIBILITIES—Level up your offering

- Produce a wide range of signage and décor jobs including applications with thin film and papers.
- Deliver stunning prints with vivid colours, smooth gradients, and sharp text at 14 m<sup>2</sup>/hr.<sup>1</sup>
- Simple finishing, lamination, and installation with flexible inks and prints that come out dry.

### EFFORTLESS—Get it done quickly and easily

- Find peace of mind with automatic maintenance processes and user-replaceable printheads.
- Save space and time with fast and automated frontloading system.
- Easily reprint projects with job storage in the printer up to 10 GB.
- Monitor your printer from anywhere and expand your capabilities with the cloud-based HP PrintOS app.

#### GO BEYOND—Lead with environmental certifications<sup>2</sup>

- Contribute to a comfortable<sup>3</sup> working environment with water-based HP Latex Ink technology.
- Differentiate your business with environmental certifications<sup>2</sup>—including UL ECOLOGO®4 and EPEAT5.
- Reduce your plastics consumption with cartonbased cartridge<sup>6</sup> and labelless supplies; free recycling via HP Planet Partners.

## For more information, please visit https://www.hp.com/go/latex-630

## Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://lkc.hp.com/

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

<sup>1</sup> Standard mode (Generic SAV Calendar) 6-pass, 6 colours, 110% ink density. Based on internal HP testing on MACTAC JT 8500 WG-PG. Print speed may vary due to the adaptive printing mechanism, which is designed to

Eased on internal competitive analysis with public information. Applicable to HP Latex technology compared to competitive large format printing alternatives using solvent and UV technologies. See individual product data sheets for more information at http://hp.com/go/latex

Based on odor sensory evaluation when printing with the HP Latex 630 series printer and Mimaki UJV 100-160. Tests done in a 57 sqm room with 5ACH. Test conducted by Odournet following the standard VDI3882,

where the HP Latex 630 series air quality were characterized, when Printing, as "neutral" for hedonic tone compared to the Mimaki UIC 100-160.

4 UL ECOLOGO® Certified HP 832 Latex inks meet a range of stringent human health and environmental considerations. For certifications, see http://www.ul.com/EL and http://www.ul.com/gg

<sup>&</sup>lt;sup>5</sup> Applicable to select HP Latex printers. EPEAT registered where applicable/supported. See http://epeat.net for registration status by country.

<sup>6</sup> Applicable to HP 832. Plastic reduction based on moving from plastic ink cartridge to cardboard ink cartridges, with annual manufacturing saving of 33 tons of plastic based on average units of HP 831 and HP 831A ink

cartridges from 2018 to 2020.

7 Visit http://hp.com/recycle to see how to participate and for HP Planet Partners program availability; program may not be available in your jurisdiction. Where this program is not available, and for other consumables not included in the program, consult your local waste authorities on appropriate disposa

## **Technical specifications**

Printing modes	35 m²/hr - Max Speed (2-pass) 18 m²/hr - Speed (4-pass) 14 m²/hr - Standard (6-pass) 11 m²/hr - Quality (8-pass) 18 m²/hr - High Saturation (12-pass) 8 m²/hr - High Saturation (12-pass)
Print resolution	7 m²/hr - Standard for Backlits and Textiles (14-pass) <sup>1</sup> Up to 1200 x 1200 dpi
Ink types	Water-based HP Latex Inks
Ink cartridges	8 (black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer, HP Latex Overcoat)
Cartridge size	1L
Printheads	5 (1 cyan/black, 1 magenta/yellow, 1 light cyan/light magenta, 1 HP Latex Optimizer, 1 HP Latex Overcoat)
Long-term print-to-print repeatability	95% of colors < 3 dE2000 <sup>2</sup>
Media	
Handling	Roll feed, take-up reel, automatic horizontal cutter (for vinyl, banner and canvas <sup>3</sup> , paper-based media, and film)
Media types	Banners, self-adhesive vinyls, films, papers, wallcoverings, canvas, synthetics, (fabrics, mesh, textiles, and any other porous materials require a liner)
Roll size	457 to 1625-mm rolls (580 to 1625-mm rolls with full support)
Maximum roll weight	42 kg
Maximum roll diameter	250 mm
Thickness	Up to 0.5 mm
Applications	Banners, Customizable clothing, Displays, Exhibition and event graphics, Exterior signage, Floor graphics, Indoor posters, Interior decoration, Labels and stickers, Light boxes - film, Light boxes - paper, POP/POS, Posters, Vehicle graphics, Wall decals, Window graphics
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T)
Dimensions (W x D	) x H)
Printer	2603 x 844 x 1405 mm
Shipping	2800 x 1130 x 1271 mm
Operating area	2793 x 2100 mm
Weight	
Printer	230 kg
Shipping	347 kg
What's in the box	HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, HP SAI Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor
	holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor
Environmental ran	holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor
Environmental ran	holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor
Environmental ran Operating temperature Operating humidity	holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor  IGES  15 to 30°C
Environmental ran Operating temperature Operating humidity Acoustics	holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor  IGES  15 to 30°C
Environmental ran Operating temperature Operating humidity Acoustics Sound pressure	holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor  Iges  15 to 30°C  20 to 80% RH (non-condensing)
Environmental ran Operating temperature Operating humidity Acoustics Sound pressure	holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor  iges  15 to 30°C  20 to 80% RH (non-condensing)  55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)
Environmental ran Operating temperature Operating humidity Acoustics Sound pressure Sound power Power	holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor  iges  15 to 30°C  20 to 80% RH (non-condensing)  55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)
Environmental ran Operating temperature Operating humidity Acoustics Sound pressure Sound power Power Consumption	holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor  Iges  15 to 30°C  20 to 80% RH (non-condensing)  55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)  7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep)
Environmental ran Operating temperature Operating humidity Acoustics Sound pressure Sound power Power Consumption Requirements	holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor  Iges  15 to 30°C  20 to 80% RH (non-condensing)  55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)  7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep)  0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <4.5 W <sup>4</sup> (sleep) (<15 W <sup>5</sup> with DFE)  Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max
Environmental ran Operating temperature Operating humidity Acoustics Sound pressure Sound power Power Consumption Requirements Certification	holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor  Iges  15 to 30°C  20 to 80% RH (non-condensing)  55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)  7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep)  0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <4.5 W <sup>4</sup> (sleep) (<15 W <sup>5</sup> with DFE)  Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max
Environmental ran Operating temperature Operating humidity Acoustics Sound pressure Sound power Power Consumption Requirements Certification Safety	purgers, 2-in spindle adaptor  Iges  15 to 30°C  20 to 80% RH (non-condensing)  55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)  7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep)  0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <4.5 W <sup>4</sup> (sleep) (<15 W <sup>5</sup> with DFE)  Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord
What's in the box  Environmental ran Operating temperature Operating humidity  Acoustics Sound pressure Sound power Power Consumption Requirements  Certification Safety Electromagnetic Environmental	holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor  Iges  15 to 30°C  20 to 80% RH (non-condensing)  55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)  7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep)  0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <4.5 W <sup>4</sup> (sleep) (<15 W <sup>5</sup> with DFE)  Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord  IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC)  Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EWC Directive), Australia and

## **Ordering information**

#### Product

171528	HP Latex 630 Printer	
Accessories		
171K8A	HP Latex 630 Output Platen Protector Accessory	
21V10A 421S3A	HP Latex 600/700/800 User Maintenance Kit HP Latex Media Feed Accessory	
7HR19A	HP Latex Media Feed Accessory  HP Latex 630/700/800 Media Loading Accessory	

#### Original HP printing supplies

4UU94A	HP 836 Optimizer Latex Printhead
4UV05A	HP 832Y 1-liter Black Latex Ink Cartridge
4UV06A	HP 832Y 1-liter Cyan Latex Ink Cartridge
4UV07A	HP 832Y 1-liter Magenta Latex Ink Cartridge
4UV08A	HP 832Y 1-liter Yellow Latex Ink Cartridge
4UV79A	HP 832 1-liter Light Cyan Latex Ink Cartridge
4UV80A	HP 832 1-liter Light Magenta Latex Ink Cartridge
4UV81A	HP 832 1-liter Optimizer Latex Ink Cartridge
4UV82A	HP 832 1-liter Overcoat Latex Ink Cartridge
4UV95A	HP 836 Black/Cyan Latex Printhead
4UV96A	HP 836 Magenta/Yellow Latex Printhead
4UV97A	HP 836 Light Cyan/Light Magenta Latex Printhead
4UV98A	HP 836 Overcoat Latex Printhead
4UV99A	HP Latex Maintenance Cartridge
	•

#### Original HP large format printing materials

HP Recycled<sup>6</sup> Removable Adhesive Fabric, 3-in Core (Latex/solvent): REACH compliant<sup>7</sup>
HP Recycled<sup>6</sup> Satin Canvas, 3-in Core (Latex/solvent): REACH compliant<sup>7</sup>
HP Premium Poster Paper: FSC<sup>6</sup> certified<sup>9</sup>
HP PVC-free<sup>10</sup> Wall Paper: UL GREENGUARD GOLD Certified<sup>11</sup>, FSC<sup>6</sup> certified<sup>9</sup>, meets AgBB criteria<sup>12</sup> HP Permanent Gloss Adhesive Vinyl: REACH compliant HP Prime Gloss Air GP: REACH compliant

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

#### Service and Support

U60QHE HP 2 year Plus Service Plan Hardware Support w/DMR U60QJE HP 3 year Plus Service Plan Hardware Support w/DMR U60QLE HP 5 year Plus Service Plan Hardware Support w/DMR U600MPE HP 1 year Post Warranty Plus Service Plan Hardware Support w/DMR U600NPE HP 2 year Post Warranty Plus Service Plan Hardware Support w/DMR



















Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects. Print mode names may vary depending on the media or application.

The color variation between printed jobs has been measured at 12 pass mode on vinyl media. Reflective measurements on a 943 color target under (IE standard illuminant DSO, and according to the standard ICEDE2000 as per CIE Draft Standard DS 014-6/E-2012. 5% of colors may experience variations above 3 dE2000. Backlit substrates measured in transmission mode may yield different results.

Automatic horizontal cutter is for use with thinner banners and canvas only. It is recommended to perform a test.

Excluding Type 2 DFE (Digital Front End) as defined in Energy Star<sup>48</sup> Product Specification for Imaging Equipment version 3.1.

Total power measured in sleep mode including the Digital Front End contained on the product consists of PET fabric and coatings. With liner attached, 72% by weight of the product consists of recycled content. Base material fabric is made from 100% recycled resin.

As of the date of this document, this product does not contain any of the chemicals on the EU's Candidate List for Authorization (otherwise known as Substances of Very High Concern) in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Article 33 Declaration published at HP Printing Products and Consumable Supplies.

determine the status of SVHC in HP products, see the HP REACH Article 33 Declaration published at the Finning Products and Consumable Supplies.

8 62% by weight of the product consists of recycled content. Base material fabric is made from 100% recycled resin. Certified according to Global Recycled Standard (GRS) Version 3.0, March 2017.

9 Trademark license code FSC-C115319.

10 Chemical analysis demonstrated elemental chlorine to be below 200 ppm. Presence of chlorine is attributed to residual chlorine used in the papermaking process, and not due to the presence of PVC.

1 HP PVC-free Wall Paper printed with HP Latex links is UL GREENGUARD GOLD Certified. UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit http://ul.com/gg. 12 With HP Latex links, prints meet AgBB criteria for health-related evaluation of VOC emissions. See http://with HP Latex links, prints meet AgBB criteria for health-related evaluation of VOC emissions.

evaluation-of-building