

Material Safety Data Sheet

1. Company identification

1.1 Company: **Fabbxible Technology**

1.2 Address: **11A, Jln. IKS Bukit Tengah, Tmn. IKS Bukit Tengah, 14000 Bukit Mertajam, Pulau Pinang, Malaysia.**

1.3 Tel: **+6017-414 7563**

2. Hazard identification

2.1 Trade Name: TPU

2.2 GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS label elements

Hazard Statement: None required
 Precautionary Statement: None
 Signal word: None
 Pictogram: None

Other hazards

If small particles are generated during further processing, handling, or by other means, combustible dust concentrations in air may form. See Section 7 and 8 for additional information.

3. Composition/Information on Ingredients

Hazardous components

Hazardous components	Content %	CAS NO:	Attribute
None	Not applicable	None	Mixture

4. First-aid measures

If inhaled : Essentially no fumes will be released from heated material, if respiratory irritation occurred immediately remove a person to fresh air and consult a doctor.

In case of skin contact : Contact with heated material, rinse the skin with water and soap for at least 15 minutes. If symptoms persist, consult a doctor.

In case of eye contact : Contact with material, rinse opened eye for at least 15 minutes with plenty of water. If symptoms persist, consult a doctor.

- If swallowed : Drink water as a precaution. Never give anything by mouth to an unconscious person. Do not induce vomiting without medical advice. Call a physician immediately.
- Notes to physician : Treat symptomatically.

5. Fire-fighting measures

- Suitable extinguishing media : Foam, Water, Carbon dioxide (CO₂), Dry chemical, Alcohol resistant foams are preferred if available. General-purpose synthetic foams (including AFFF) or protein foams may function, but much less effectively.
- Specific hazards during firefighting : Do not allow run-off from firefighting to enter drains or water courses.
- Hazardous combustion products : Burning produces obnoxious and toxic fumes, hydrogen cyanide (HCN), acrylonitrile (AN), styrene (SM), carbon monoxide (CO), carbon dioxide (CO₂), Nitric oxide (NO).
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents. Remove the flammability.
- Under fire conditions : Cool containers / tanks with water spray. Water mist may be used to cool closed containers. Fine dust dispersed in air may ignite. Risks of ignition followed by flame propagation or secondary explosions shall be prevented by avoiding accumulation of dust, e.g. on floors and ledges.
- Special protective equipment for firefighters : As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Avoid contact with skin and eyes. Avoid dust formation. Remove all sources of ignition. Sweep up to prevent slipping hazard.
- Environmental precautions : Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system.
- Methods and materials for containment and cleaning up : Clean up promptly by scoop or vacuum. Sweep up and shovel into suitable containers for disposal.

7. Handling and storage

- Advice on safe handling : Use personal protective equipment. Avoid contact with skin and eyes. Low hazard for usual industrial or commercial handling. Workers should be protected from the possibility of contact with molten material during fabrication. Avoid dust formation. If small particles are generated during further processing, handling, or by other means, combustible dust concentrations in air may form.
- Conditions for safe storage : Store at cool, ventilated cool and ventilated place. No special restrictions on storage with other products.
- Materials to avoid : No special precautions required.

8. Exposure Control/Personal Protection

Exposure limits:

None established. This material can generate Particulates Not Otherwise Classifiable (PNOC). The Occupational Safety and Health Administration (OSHA) PEL/TWA for PNOC is 15 mg/m³ for total dust and 5 mg/m³ for the respirable fraction. The American Conference of Governmental Industrial Hygienists (ACGIH) TLV/TWA for PNOC is 10 mg/m³ for inhalable particulates and 3 mg/m³ for respirable particulates.

- Engineering measures** : Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide appropriate exhaust ventilation at places where dust is formed.

Personal protective equipment

- Respiratory protection : Respirator must be worn if exposed to dust. Wear respirator with dust filter. Consult an industrial hygiene professional prior to respirator selection and use. Use a positive-pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.
- Eye protection : Safety glasses with side-shields. Goggles.
- Skin and body protection : Impervious clothing.
- Hygiene measures : Observe good industrial hygiene practices. Avoid contact with skin, eyes and clothing.

9. Physical and chemical properties

- Physical state : Solid
- Odour : None

Diameter	:	1.75/3.00mm
Decomposition temperature	:	>300 °C
Density	:	0.87~1.00 g/cm ³
Water solubility	:	Insoluble

10. Stability and reactivity

Reactivity	:	None expected under conditions of normal use.
Chemical stability	:	Stable under recommended storage conditions.
Possibility of hazardous reactions	:	Product will not undergo hazardous polymerization.
Incompatible materials	:	Oxidizing agents, Strong bases
Hazardous decomposition products	:	Burning produces obnoxious and toxic fumes, carbon monoxide (CO), carbon dioxide (CO ₂), Nitric oxide (NO).

11. Toxicological information

Information on likely routes of exposure	:	Inhalation Skin contact Eye Contact Ingestion
--	---	--

Acute toxicity

There were no target organ effects noted following ingestion or dermal exposure in animal studies.

Skin corrosion/irritation/

Product dust may be irritating to eyes, skin and respiratory system.

Serious eye damage/eye irritation

Product dust may be irritating to eyes, skin and respiratory system. Resin particles, like other inert materials, are mechanically irritating to eyes.

Respiratory or skin sensitization

Product dust may be irritating to eyes, skin and respiratory system.

Germ cell mutagenicity

Not mutagenic in AMES Test.

Carcinogenicity

None of the components of this product are listed as carcinogens by IARC, NTP, or OSHA.

Reproductive toxicity

No data is available on the product itself.

STOT - single exposure

There were no target organ effects noted following ingestion or dermal exposure in animal studies.

STOT - repeated exposure

There were no target organ effects noted following ingestion or dermal exposure in animal studies.

Aspiration toxicity

Inhalation of dust may cause shortness of breath, tightness of the chest, a sore throat and cough.

Burning produces irritant fumes.

12. Ecological information

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : EC50/72h/algae > 1100 mg/L

Persistence and degradability

Inherently biodegradable under industrial composting conditions

Bioaccumulative potential

Not expected to bioconcentrate or bioaccumulate.

13. Disposal considerations

Disposal methods

General advice : In accordance with local and national regulations. Should not be released into the environment. Do not contaminate ponds, waterways or ditches with chemical or used container. Contact manufacturer.

Contaminated packaging : Empty containers should be transported/delivered using a registered waste carrier to local recyclers for disposal.

14. Regulatory information

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Component(s)SARA 313

California Prop 65 This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory
DSL : All components of this product are on the Canadian DSL
AUSTR : On the inventory, or in compliance with the inventory
ENCS : On the inventory, or in compliance with the inventory
KECL : On the inventory, or in compliance with the inventory
PHIL : On the inventory, or in compliance with the inventory
IECSC : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECL (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15. Other information

Please call to (60)17 414 7563 or visit to our website: www.fabbxible.com

Important:

All information on this data sheet is based on the present state of our knowledge and does not guarantee of any kind of usage, application or purpose, whether implied or expressed since conditions of use are outside our control. It is provided for your guidance only. For your particular purpose, we recommend that you make tests to determine the suitability of a product prior to use. Each customer should establish his own rules and take proper steps appropriate to the circumstances within his control and must take responsibility for observing existing laws and regulations. This Data Sheet does not form part of the conditions of sale of our products and is of a general nature.

End of data sheet