





Exmor™ high-sensitivity image sensor

The DrivePro 230 uses an Exmor™ sensor to capture high-resolution images with superb, rich color even in low light. Its built-in Wide Dynamic Range (WDR) technology balances the light and dark areas of captured images, ensuring that every critical shot is as clear as possible.



GPS/GLONASS receiver

The DrivePro 230's GPS/GLONASS receiver can log coordinates, date, and time into recorded video footage. The coordinates precisely locate where an incident happened so that emergency road services, police, or an insurance representative can respond more quickly.



Handy snapshot function

The snapshot button allows you to take photos while still recording video.
During an incident, you can remove the DrivePro 230 from the vehicle to create a photographic record of collision damage.





Dashcams

DrivePro™ 230

Features

- · Exmor™ high-sensitivity image sensor
- Built-in GPS/GLONASS receiver logs your driving path
- Built-in Wi-Fi function for mobile live streaming
- Built-in battery ensures uninterruptible recording
- Parking mode and time-lapse video safeguard your vehicle continuously



DrivePro Toolbox Software

The DrivePro Toolbox is developed for Transcend DrivePro series. Featured a user-friendly interface, the DrivePro Toolbox allows you to select and play videos recorded on your DrivePro Car Video Recorder without the need to install separate codecs.

Specification

Αр	р	е	а	r	а	r	١	C	е
----	---	---	---	---	---	---	---	---	---

Dimensions	70.2 mm x 63.1 mm x 34.5 mm (2.76" x 2.48" x 1.36")
Weight	81 g (2.86 oz)

Interface

The contract				
USB Type	micro USB to car lighter adapter			
Connection Interface	USB 2.0			
Network Interface	Wi-Fi 802.11n			

Hardware

Display	2.4" color TFT LCD			
Viewing Angle for Lens	130° (diagonal)			
Aperture	F/2.0			

Operating Environment

Operating Temperature	-20°C (-4°F) ~ 65°C (149°F)
Storage Temperature	-25°C (-13°F) ~ 70°C (158°F)
Input Voltage	12V ~ 24V
Output Voltage	5V / 1A

Format

Resolution	Full HD 1080P
Frame Rate	30 fps
Video Format	MOV (H.264)

Warranty

,	
Certificate	CE/FCC/BSMI/NCC/MIC/KC/EAC
Warranty	Two-year Limited Warranty

Ordering Information

Product specifications are subject to change without notice. Pictures shown may differ from actual products. When used as a storage capacity unit, one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment.



Dashcams Comparison







DrivePro™ 230



DrivePro™ 110



DrivePro™ 10

Appearance					
Dimensions (Max.)	95.6 mm x 65.9 mm x 40.5 mm	70.2 mm x 63.1 mm x 34.5 mm	70.2 mm x 63.1 mm x 32.5 mm	58.3mm x 36mm x 22.8mm	
Weight (Max.)	107 g (3.77 oz)	81 g (2.86 oz)	69g (2.43 oz)	40g (1.41 oz)	
Interface					
USB Type	micro USB to car lighter adapter				
Connection Interface	USB 2.0	USB 2.0	USB 2.0	USB 2.0	
Network Interface	Wi-Fi 802.11n		Wi-Fi 802.11n		
Hardware					
Display	2.4" color TFT LCD	2.4" color TFT LCD	2.4" color TFT LCD	-	
Viewing Angle for Lens	160° (diagonal)	130° (diagonal)	140° (diagonal)	140° (diagonal)	
Viewing Angle for Rear Lens	110° (diagonal)	-	-	-	
Aperture	F/2.2	F/2.0	F/2.0	F/2.0	
Aperture (Rear)	F/2.8	-	-	-	
Image Sensor	Exmor™	Exmor™	STARVIS™	STARVIS™	
Infrared LEDs	V	-	-	-	
GPS Coordinates	V	V	-	-	
Dual Lens Camera	V	-	-	-	
Built-in Battery	V	V	V	V	
G-Sensor	V	V	V	V	
Snapshot	V	V	V	-	
Microphone	V	V	V	V	
Speaker	V	V	V	-	
Wi-Fi	V	V	-	V	
Format					
Resolution	Full HD 1080P	Full HD 1080P	Full HD 1080P	Full HD 1080P	
Resolution (Rear)	HD 720P	-	-	-	
Frame Rate	30 fps	30 fps	30/60 fps	30/60 fps	
Video Format	.MP4 (H.264)	.MOV (H.264)	.MP4 (H.264)	.MP4 (H.264)	
Technology					
Lane Departure Warning System	V	V	-	-	
Forward Collision Warning System	V	V	-	-	
Head-up display	V	V	-	-	
Headlight reminder	V	V	V	-	
Driver fatigue alert	V	٧	V	-	
Emergency recording	٧	V	V	V	

Note: Exmor/STARVIS is a trademark of Sony Corporation.