

Premium Performance

PREMIUM

MID-RANGE

ECONOMY

PREMIUM MATERIALS HANDLING RESILIENT

TRELLEBORG
M²



PREMIUM MATERIALS HANDLING RESILIENT

TRELLEBORG M2

Trelleborg M² is a premium, solid, resilient tire designed for demanding materials handling environments. For forklift trucks that are in heavy use or routinely carrying heavy loads, Trelleborg M²'s design and construction ensures maximum performance.

Trelleborg M² resilient tires feature the Pit Stop Line wear indicator. The Pit Stop Line ensures that users get maximum whole-life value from their choice of tire by always replacing them at the right time and being able to keep forklift downtime to a minimum, as well as always knowing that their tires are safe to use.



Tire Size	Alternative Size	Rim Size	Additional Pattern	LOC	Tire Dimensions [mm]		Load Capacity [kg]		
							Static	Forklift trucks up to 25 km/h	
					Overall Diameter	Section Width		Load Wheel	Steering Wheel
10½x4-6*		3.25I-6	Ribbed only		268	104	710	610	470
4.00-8		2.50-8	Ribbed		408	104	1100	950	730
4.00-8		3.00D-8	Ribbed	•	408	104	1100	950	730
4.00-8 *		3.56-8	Ribbed only		408	125	1170	1010	775
4.00-8		3.75P-8			408	125	1170	1010	775
15x4½-8	125/75-8	3.00D-8	Ribbed	•	376	117	1210	1040	800
5.00-8		3.00D-8		•	457	122	1650	1415	1090
5.00-8		3.75P-8	Ribbed		457	152	1740	1495	1150
16x6-8	150/75-8	4.33R-8	Ribbed	•	411	152	1740	1495	1150
17x7-8 *		4.33R-8	Smooth only		430	159	2160	1860	1430
18x7-8	180/70-8	4.33R-8		•	457	157	2490	2145	1650
18x9-8		7.00-8	Smooth		457	207	2870	2470	1900
140/55-9	15x5.5-9	4.00E-09		•	373	132	1360	1170	900
6.00-9		4.00E-09		•	526	140	2190	1885	1450
6.00-9		4.00E-09	Ribbed		526	140	2190	1885	1450
21x8-9	200/75-9	6.00E-09		•	518	185	3200	2755	2120
6.50-10		5.00F-10		•	577	160	2720	2340	1800
6.50-10		5.50F-10			577	160	2720	2340	1800
180/60-10		5.00F-10		•	458	157	2795	2410	1850
200/50-10		6.50F-10		•	456	197	2870	2470	1900
23x9-10	225/75-10	6.50F-10		•	584	201	4000	3445	2650
7.00-12		5.00S-12	Smooth	•	650	173	3380	2920	2240
23x10-12	250/60-12	8.00G-12		•	587	239	4380	3770	2900
27x10-12	250/75-12	8.00G-12		•	678	239	4530	3900	3000
315/45-12		10.00G-12		•	572	279	5210	4485	3450
7.00-15	29x8-15	5.5-15		•	729	180	4115	3545	2725
7.50-15		5.5-15			747	193	4530	3900	3000
7.50-15		6.5-15			747	193	4530	3900	3000
8.25-15		5.5-15			808	208	5360	4615	3550
8.25-15		6.5-15		•	808	208	5510	4750	3650
28x9-15	225/75-15	6.5-15			693	224	4530	3900	3000
28x9-15	225/75-15 (8.15-15)	7.0-15		•	693	224	4530	3900	3000

THE PIT STOP LINE

Choosing Pit Stop Line tires ensures that customers always get maximum value by replacing tires at the right time. As the tire tread wears down, a highly visible orange stripe appears on the tire surface indicating approximately 100 hours of tire life remaining. This allows ample time to schedule replacement at your convenience without compromising performance, safety or productivity.



Tire Size	Alternative Size	Rim Size	Additional Pattern	LOC	Tire Dimensions [mm]		Load Capacity [kg]		
							Static	Forklift trucks up to 25 km/h	
					Overall Diameter	Section Width		Load Wheel	Steering Wheel
250-15	250/70-15	7.0-15		•	711	221	5510	4745	3650
250-15	250/70-15	7.5-15			711	221	5510	4745	3650
280/50-15		8.0-15	Ribbed	•	670	255	6040	5200	4000
300-15	315/70-15	8.0-15		•	813	257	6795	5850	4500
400/60-15		11.0-15	VP15 only		815	325	10420	8970	6900
355/45-15	28x12½-15	9.75-15		•	683	288	6610	5690	4375
355/50-15		9.75-15		•	711	284	6610	5690	4375
355/65-15	32x12½-15 (350-15)	9.75-15		•	808	282	9060	7800	6000
7.50-16		5.5-16			808	208	4645	4000	3075
9.00-20		6.5-20			973	221	6795	5400	4500
10.00-20	270/95-20	6.5-20			1011	249	7360	5850	4875
10.00-20	290/95-20	8.0-20			1011	249	7550	6000	5000
12.00-20	290/95-20	8.0-20	Smooth		1092	259	9515	7560	6300
12.00-20	330/95-20	8.5-20			1092	259	9515	7560	6300
12.00-20	330/95-20	10.0-20	Smooth		1090	312	9815	7800	6500
355/50-20		10.0-20	Smooth	•	833	310	10420	8970	6900

* Traction pattern not available

SPECIAL COMPOUNDS AVAILABLE

NM

Non-Marking

EC

Electrically Conductive

HL

High Load


CR

Cut Resistant

SC

Chemical Resistant (Scrubber)

TREAD PATTERNS



Five reasons to choose Pit Stop Line



MAXIMUM VALUE

Choosing Pit Stop Line means never replacing tires too early and always being in control of tire spend.



MAXIMUM UPTIME

Pit Stop Line tires are built to perform and last. Premium design, construction and compounding increase productivity.



ENHANCED SAFETY

Choosing Pit Stop Line tires means never replacing tires too late, protecting operators and machines.



REDUCED IMPACT

Choosing Pit Stop Line tires means using fewer tires and reducing carbon footprint.



SERVICE MADE EASY

Choosing Pit Stop Line tires means having plenty of time to schedule replacement at the right time.



TRELLEBORG