

Your First Choice Solution Provider

DESIGNED FOR EXCELLENT LIFESTYLE COMFORT

How to improve housing water pressure using a booster pump?
Introducing CNP CHLF(T)-PC, experience a modern comfort & superior quality of domestic booster pump.

CNP CHLF(T)-PC provides instant water supply with strong and constant pressure to meet your daily needs, comprising ideal of instant water heater showers, flushing point, tap and garden.

CNP CHLF(T)-PC couple with CNP press control is an electronic device to ensure optimum control of automatic water pressure pump.

Main pump components are manufactured from stainless steel 304 for longer life span.

LIVING COLLECTION

居家首選好件

24
MONTHS*
WARRANTY



CHLF - PC



CHLF(T) - PC



CHL - PC

DOMESTIC BOOSTER PUMP



find us on | facebook.

TECHNICAL DATA


MODEL	INLET/ OUTLET	POWER (kW)	OUTPUT : m3/hr													
			1.0	1.5	2.0	2.5	3.5	5.0	8.0	11.0	14.0	16.0	18.0	22.0	24.0	28.0
			DISCHARGE PRESSURE : bar													
2-30PC	1" / 1"	0.37	2.65	2.45	2.2	1.9	1.2									
2-50PC	1" / 1"	0.55	4.3	4.0	3.6	3.15	2.05									
4-30PC	1 1/4" / 1"	0.55	2.8	2.74	2.7	2.65	2.48	2.05								
4-40PC	1 1/4" / 1"	0.75	3.75	3.66	3.6	3.5	3.23	2.7								
8-30PC	1 1/2" / 1 1/4"	1.1						2.75	2.7	2.1						
8-40PC	1 1/2" / 1 1/4"	1.5						3.9	3.5	27.5						
12-30PC	1 1/2" / 1 1/4"	1.8							3.45	3.1	4.4	2.0				
16-20PC	2" / 1 1/4"	2.2									2.3	2.17	2.0	1.55		
20-20PC	2" / 1 1/4"	2.2											2.35	2.05	1.85	1.45

* For CHL-PC series Connection is 2" / 1 1/4"

TECHNICAL SPECIFICATIONS

MODEL	MAX. AMBIENT TEMPERATURE	MAX. LIQUID TEMPERATURE	MAX. OPERATING PRESSURE	FITTING
2-30PC	Up to +40°C	Up to +70°C	10 bar	1/2" X 1/2"
2-50PC	Up to +40°C	Up to +70°C	10 bar	1/2" X 1/2"
4-30PC	Up to +40°C	Up to +70°C	10 bar	1/2" X 1/2"
4-40PC	Up to +40°C	Up to +70°C	10 bar	1/2" X 1/2"
8-30PC	Up to +40°C	Up to +70°C	10 bar	1/2" X 1/2"
8-40PC	Up to +40°C	Up to +70°C	10 bar	1/2" X 1/2"
12-30PC	Up to +40°C	Up to +70°C	10 bar	1/2" X 1/2"
16-20PC	Up to +40°C	Up to +70°C	10 bar	1/2" X 1/2"
20-20PC	Up to +40°C	Up to +70°C	10 bar	1/2" X 1/2"

UNION COUPLINGS (FOR EASY DISMANTLING AND SERVICE)



CHLF - PC



CHLF (T) - PC



CHL - PC



5 ADVANTAGES



QUIET OPERATION



LONGER LIFE SPAN



ENERGY SAVING



QUALITY ASSURANCE



EASY INSTALLATION

