## **SCALA2**

# Pressure boosting. Like never before.

With the new generation **SCALA2**, we unveil the next era of integrated booster solutions with pioneering technology for constant water pressure, low noise, and energy efficiency.

An innovative all-in-one pressure-boosting solution, engineered to guarantee more reliable operations in homes and apartments.



### **Benefits for installers**



#### **Easy installation**

Ready and tool-free installation out of the box with user-friendly HMI for quick setup.



#### **Easy selection**

With only one product variant and size for all domestic applications, it's easy to always keep one in the van or at the company warehouse.



#### **Compact all-in-one booster**

Fully integrated water pressure booster in compact and robust design minimizes space limitations.



#### **Product support**

Grundfos provides strong product support to ensure you gain a comprehensive understanding of the new SCALA2.

Our support includes online installation and training videos, along with comprehensive technical documentation.





#### Constant water pressure in up to 8 taps

With integrated controls and a frequency-driven motor, the pump delivers perfect water pressure to all taps, automatically adjusting to your customers' demands.



#### The most silent operation in the market

Utilizing state-of-the-art technology, the new SCALA2 is one of the world's quietest pressure boosters. Operating at a noise level as low as 44 dB(A) (equivalent to the noise level of a quiet dishwasher) every family member will enjoy peace and quiet around the clock.




#### World-class energy performance

Equipped with improved hydraulics, a permanent magnet motor and speed control, the SCALA2 outperforms many other domestic water pressure booster in the market. This ensures homeowners can optimise consumption and save energy and costs.




Possibility in every drop




Technical details	SCALA2
Noise	44 dB(A)
Max. ambient temperature	55°C (131°F)
Max. liquid temperature	45°C (113°F)
Max. system pressure	10 bar (145 psi)
Max inlet pressure	6 bar (87 psi)
Max head	45 m (147ft)
IP rating	X4D (outdoor installation)
Floors	Max. 3
Taps	Max. 8
Power input P1	550 W
Rated power P2	450 W
Dimensions	H: 302 mm (11.9 inch) L: 403 mm (15.9 inch) W: 193 mm (7.6 inch)
Weight	10 kg (21.3 lb)
Approvals for drinking water	WRAS, ACS,NSF, AWQC, Kiwa tech, UBA, UL

## A booster pump for all installation types

SCALA2 uses groundbreaking technology to integrate essential pressure-boosting components into a single compact enclosure. Other key features make it versatile for various installations:





#### Tank or shallow well

Self-priming, de-air function, and dry running protection guarantee a steady water supply from shallow wells or underground tanks. It can lift water from up to 8 m depth.

#### **Roof tank**

The pump ensures precise control and setpoint adjustment for optimal water pressure when boosting from a tank. Its IPx4D rating allows installation both indoors and outdoors.

\* Note: Some country regulations might impose limitation to the installation. Please make sure to follow local rules and regulations. Learn more and see all details at Grundfos.com/my



#### **GRUNDFOS PUMPS SDN BHD (202527-A)**

7, Jalan Peguam U1/25, Glenmarie Industrial Park, 40150 Shah Alam, Selangor Tel: +603-5032 1900 | Fax: +603-5032 1732 Toll Free: 1800 88 PUMP (7867) Email: Sales\_MY@sales.grundfos.com Orders: orders\_my@grundfos.com

Service: service\_my@grundfos.com



