



Catalogue CATERING Chapter DISHWASHING

## Model

1

CO-402 COLD 230V 1N 50/60Hz

19030909

03/04/2019

CO-402 COLD DISHWASHER					∱Ζ
- Front-loading glass washers - EVO Generation	DIMENSIONS				×
<ul> <li>Front-loading glass washers - EVO Generation</li> <li>Constructed in stainless steel.</li> <li>Door with double wall.</li> <li>Double rotating wash and rinse system, top and bottom, in stainless steel.</li> <li>Rounded tank to facilitate washing and drainage.</li> <li>Stainless steel armoured heating elements in the wash tank and rinse boiler.</li> <li>Thermostatic control of temperatures (wash, 60°C, and rinse, 90°C).</li> <li>Safety thermostat</li> <li>Rinse aid doser incorporated.</li> <li>Fitted with non-return valve.</li> <li>260 W wash pump</li> <li>Water consumption per 2.2 litre cycle.</li> <li>Magnetic safety stop switch in door opening.</li> <li>Model for 400 x 400 mm baskets.</li> <li>Model with electronic control and thermostop. 90" - 120" – 180" wash cycles and maximum production of 40 baskets/hour.</li> <li>Useful internal height of 270 mm.</li> <li>Tank with volume of 15 litres, with 2.8 kW heating element.</li> <li>Tank with volume of 4 litres, with 2.8 kW heating element.</li> <li>IPX4 anti-humidity protection.</li> <li>Manual push button for final cold rinse (COLD Model)</li> </ul>	DIMENSIONS X Width Y Depth Z Height Net Weight Net volume ELECTRICITY TECH Electric power Heating power Voltage Amperage	720 35,0 0,176	mm mm kg m3	X Gross width Y Gross depth Z Gross height Gross Weight Gross volume	530 mm 680 mm 890 mm 42,0 kg 0,321 m3 3,060 kW 2,80 kW 2,80 kW 230V - 1N 13,3
	Electric frequency				50/60Hz
	WATER TECHNICAL SPECIFICATIONS				
	Pressure H2O: 2				00-400kPa(2-4bar)
	Water max consumption				50,00 L/h
	CONNECTIONS TECHNICAL SPECIFICATIONS				
	Single-phase 230V wiring			2X2,5+T - 20 A	
	Hot softened water diameter				3/4"
	Drain 1 diameter 2"				
	OTHERS				

Noise level

 $\mathbb{N}$ 

000

62,00 dB

