SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® Titanium Putty Resin

Other means of identification

SKU# 0113

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Performance Polymers

Address 30 Endicott Street

Danvers, MA 01923

United States

Telephone Customer Service 978-777-1100

Website www.itwperformancepolymers.com

E-mail Not available. **Contact person** EHS Department

Emergency phone number Chemtrec 800-424-9300

International 703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A Sensitization, skin Category 1

Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May

cause drowsiness or dizziness.

Precautionary statement

Prevention Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated

work clothing must not be allowed out of the workplace. Wear eye protection/face protection.

Wear protective gloves.

Response If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable

for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical

advice/attention. Take off contaminated clothing and wash it before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ferrosilicon, [with >= 30% But <= 70% Silicon]		8049-17-0	40 - 70
Epoxy Resin:reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)		25068-38-6	15 - 40
Other components below reportable I	evels		7 - 13

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

center or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

equipment/instructions

Specific methods

General fire hazards No

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged

exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe

good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in tightly closed container. Store away from incompatible materials (see

Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Other Wear appropriate chemical resistant clothing.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Viscous. Liquid. **Appearance**

Liquid. Physical state

Viscous. Liquid. **Form** Not available. Color

Odor Slight.

Odor threshold Not available. Not available. pН Melting point/freezing point Not available.

Initial boiling point and boiling

range

608 °F (320 °C) estimated

> 399.9 °F (> 204.4 °C) Flash point

Evaporation rate Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

(%)

Relative density

Not available.

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. Vapor pressure Not available. Not available. Vapor density Not available.

Material name: DEVCON® Titanium Putty Resin 0113 Version #: 01 Issue date: 05-29-2019

Solubility(ies)

Solubility (water) Not available. Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available. Not available. **Decomposition temperature** Not available.

Other information

Viscosity

Density 1.52 g/cm3 estimated

Explosive properties Not explosive.

Combustible IIIB estimated Flammability class

Not oxidizing. **Oxidizing properties** Specific gravity 1.52 estimated

VOC 0 g/l

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be Inhalation

harmful.

Causes skin irritation. May cause an allergic skin reaction. Skin contact

Eye contact Causes serious eye irritation.

Expected to be a low ingestion hazard. Ingestion

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms related to the physical, chemical and Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May

cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. toxicological characteristics

Information on toxicological effects

Acute toxicity Not known.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Not a respiratory sensitizer. Respiratory sensitization

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects. Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability Bioaccumulative potential

No data is available on the degradability of any ingredients in the mixture.

Mobility in soil No data available.

Other adverse effects No other adverse

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Material name: DEVCON® Titanium Putty Resin 0113 Version #: 01 Issue date: 05-29-2019

Classified hazard categories

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

05-29-2019 Issue date

Version #

United States & Puerto Rico

HMIS® ratings Health: 2

Flammability: 1 Physical hazard: 0

Health: 2 NFPA ratings

Flammability: 1 Instability: 0

ITW Performance Polymers cannot anticipate all conditions under which this information and its Disclaimer

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Material name: DEVCON® Titanium Putty Resin 0113 Version #: 01 Issue date: 05-29-2019

Yes

SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® Titanium Putty Hardener

Other means of identification

SKU# 5318N

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Performance Polymers

Address 30 Endicott Street

Danvers, MA 01923

United States

Telephone Customer Service 978-777-1100

Website www.itwperformancepolymers.com

E-mail Not available.

Contact person EHS Department

Emergency phone number Chemtrec 800-424-9300

International 703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Acute toxicity, dermal

Skin corrosion/irritation

Serious eye damage/eye irritation

Category 1

Sensitization, skin

Category 1

Category 1

Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and eye damage.

May cause an allergic skin reaction. Causes serious eye damage. May cause drowsiness or

dizziness.

Precautionary statement

Prevention Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat,

drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective

gloves/protective clothing/eye protection/face protection.

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison

center/doctor. If skin irritation or rash occurs: Get medical advice/attention.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

N	Λ	i٧	rtı	re	•

Chemical name	Common name and synonyms	CAS number	%
Ferrosilicon, [with >= 30% But <= 70% Silicon]		8049-17-0	10 - 30
Formaldehyde, Oligomeric Reaction Products With Phenol And Triethylenetetramine	1	32610-77-8	10 - 30
Glass Oxide		65997-17-3	5 - 10
Phenol		108-95-2	5 - 10
TRIETHYLENETETRAMINE		112-24-3	5 - 10
1h-imidazole, 2-ethyl-4-methyl-		931-36-2	2.5 - 10
Titanium Dioxide		13463-67-7	1 - 5
Methylimidazole, 4-		822-36-6	0.1 - 1
Other components below reportable	levels		10 - 20

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

center or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Call a physician

or poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

observation. Symptoms may be delayed.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Burning pain and severe

corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing,

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Indication of immediate

Ingestion

medical attention and special treatment needed

redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under

Ensure that medical personnel are aware of the material(s) involved, and take precautions to **General information** protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

During fire, gases hazardous to health may be formed.

Do not use water jet as an extinguisher, as this will spread the fire.

clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods General fire hazards Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Use water spray to cool unopened containers.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

Material name: DEVCON® Titanium Putty Hardener 5318N Version #: 01 Issue date: 05-29-2019

SDS US

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid prolonged exposure. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Titanium Dioxide (CAS PEL 15 mg/m3 Total dust.	Components	Туре	Value	Form
Titanium Dioxide (CAS 13463-67-7) US. OSHA Table Z-3 (29 CFR 1910.1000) Type	Phenol (CAS 108-95-2)	PEL	19 mg/m3	
13463-67-7 US. OSHA Table Z-3 (29 CFR 1910.1000)			5 ppm	
Components Type Value Form Titanium Dioxide (CAS 13463-67-7) TWA 5 mg/m3 Respirable fraction. 15 mg/m3 Total dust. 50 mppcf Total dust. 50 mppcf Respirable fraction. Respirable fraction. US. ACGIH Threshold Limit Values Type Value Components Type Value Phenol (CAS 108-95-2) TWA 10 mg/m3 Titanium Dioxide (CAS 13463-67-7) TWA 10 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards Components Value Form Glass Oxide (CAS 65997-17-3) TWA 3 fibers/cm3 Fiber. 65997-17-3) 3 fibers/cm3 Fibrous dust. 5 mg/m3 fibers, total dust 5 mg/m3 Fiber, total Phenol (CAS 108-95-2) Ceiling 60 mg/m3 Fiber, total	Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
Titanium Dioxide (CAS 13463-67-7) Titanium Dioxide (CAS 13463-67-7) Titanium Dioxide (CAS 15 mg/m3 Total dust. 50 mppcf Total dust. 15 mppcf Respirable fraction. 15 mppcf Respirable fr		0)		
15 mg/m3	Components	Туре	Value	Form
US. ACGIH Threshold Limit Values Components Type Value Phenol (CAS 108-95-2) TWA Titanium Dioxide (CAS 13463-67-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form Glass Oxide (CAS 65997-17-3) TWA 3 fibers/cm3 Fiber. 3 fibers/cm3 Fibrous dust. 5 mg/m3 Fiber, total dust 5 mg/m3 Fiber, total Phenol (CAS 108-95-2) Ceiling Form 60 mg/m3	Titanium Dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
US. ACGIH Threshold Limit Values Components Type Value Phenol (CAS 108-95-2) TWA Titanium Dioxide (CAS 13463-67-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form Glass Oxide (CAS 65997-17-3) TWA 3 fibers/cm3 Fiber. 5 mg/m3 fibers, total dust 5 mg/m3 Fiber, total Phenol (CAS 108-95-2) Ceiling Respirable fraction. Respirable fraction. Respirable fraction. Respirable fraction. Respirable fraction. Respirable fraction. Sibure Value Form 6 ong/m3 Fiber. 6 ong/m3			15 mg/m3	Total dust.
Value			50 mppcf	Total dust.
Components Type Value Phenol (CAS 108-95-2) TWA 5 ppm Titanium Dioxide (CAS 13463-67-7) TWA 10 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form Glass Oxide (CAS 65997-17-3) TWA 3 fibers/cm3 Fiber. 65997-17-3) Fibrous dust. 5 mg/m3 Fiber, total dust Phenol (CAS 108-95-2) Ceiling 60 mg/m3			15 mppcf	Respirable fraction.
Phenol (CAS 108-95-2) TWA 5 ppm Titanium Dioxide (CAS 13463-67-7) 10 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form Glass Oxide (CAS 65997-17-3) TWA 3 fibers/cm3 Fiber. 65997-17-3) 3 fibers/cm3 Fibrous dust. 5 mg/m3 fibers, total dust Phenol (CAS 108-95-2) Ceiling 60 mg/m3	US. ACGIH Threshold Limit Values			
Titanium Dioxide (CAS 13463-67-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form Glass Oxide (CAS 65997-17-3) TWA 3 fibers/cm3 Fiber. 5 mg/m3 fibers, total dust 5 mg/m3 Fiber, total Phenol (CAS 108-95-2) Ceiling 60 mg/m3	Components	Туре	Value	
US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form Glass Oxide (CAS 65997-17-3) TWA 3 fibers/cm3 Fiber. 65997-17-3) 3 fibers/cm3 Fibrous dust. 5 mg/m3 fibers, total dust Phenol (CAS 108-95-2) Ceiling 60 mg/m3 Fiber, total	Phenol (CAS 108-95-2)	TWA	5 ppm	
ComponentsTypeValueFormGlass Oxide (CAS 65997-17-3)TWA3 fibers/cm3Fiber.3 fibers/cm3Fibrous dust.5 mg/m3fibers, total dust5 mg/m3Fiber, totalPhenol (CAS 108-95-2)Ceiling60 mg/m3	Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Glass Oxide (CAS 65997-17-3) TWA 3 fibers/cm3 Fiber. 3 fibers/cm3 Fibrous dust. 5 mg/m3 fibers, total dust 5 mg/m3 Fiber, total Phenol (CAS 108-95-2) Ceiling 60 mg/m3	US. NIOSH: Pocket Guide to Chemical	Hazards		
65997-17-3) 3 fibers/cm3 Fibrous dust. 5 mg/m3 fibers, total dust 5 mg/m3 Fiber, total Phenol (CAS 108-95-2) Ceiling 60 mg/m3	Components	Туре	Value	Form
5 mg/m3 fibers, total dust 5 mg/m3 Fiber, total dust 6 mg/m3 Fiber, total Phenol (CAS 108-95-2) Ceiling 60 mg/m3	Glass Oxide (CAS 65997-17-3)	TWA	3 fibers/cm3	Fiber.
5 mg/m3 Fiber, total Phenol (CAS 108-95-2) Ceiling 60 mg/m3			3 fibers/cm3	Fibrous dust.
Phenol (CAS 108-95-2) Ceiling 60 mg/m3			5 mg/m3	fibers, total dust
			5 mg/m3	Fiber, total
15.6 ppm	Phenol (CAS 108-95-2)	Ceiling	60 mg/m3	
			15.6 ppm	

Material name: DEVCON® Titanium Putty Hardener 5318N Version #: 01 Issue date: 05-29-2019

US. NIOSH: Pocket Guide to Chemical Hazards Form Value Components Type TWA 19 mg/m3 5 ppm US. Workplace Environmental Exposure Level (WEEL) Guides Components Type Value TWA **TRIETHYLENETETRAMIN** 6 mg/m3 E (CAS 112-24-3)

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Phenol (CAS 108-95-2)	250 mg/g	Phenol with hydrolysis	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Phenol (CAS 108-95-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Phenol (CAS 108-95-2) Skin designation applies.

US - Tennessee OELs: Skin designation

Phenol (CAS 108-95-2) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Phenol (CAS 108-95-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Phenol (CAS 108-95-2) Can be absorbed through the skin.

US WEEL Guides: Skin designation

TRIETHYLENETETRAMINE (CAS 112-24-3)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Phenol (CAS 108-95-2)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

1 ppm

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with

organic vapor cartridge.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Paste.
Physical state Solid.
Form Paste.
Color Off-white.
Odor Ammoniacal.

Odor threshold Not available. Not available. pН

53.6 °F (12 °C) estimated Melting point/freezing point Initial boiling point and boiling 510.8 °F (266 °C) estimated

range

Flash point 276.1 °F (135.6 °C) estimated

Not available. **Evaporation rate** Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available.

0.001 hPa estimated Vapor pressure

Vapor density Not available. Not available. Relative density

Solubility(ies)

Not available. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

640 °F (337.78 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available. Not available. **Viscosity**

Other information

1.65 g/cm3 estimated Density

Not explosive. **Explosive properties** Oxidizing properties Not oxidizing. Specific gravity 1.65 estimated

VOC 0 g/I

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials.

Incompatible materials Peroxides. Phenols.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. May cause irritation to the

respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes severe skin burns. Harmful in contact with skin. May cause an allergic skin reaction.

Eye contact Causes serious eye damage.

Ingestion Causes digestive tract burns. Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Information on toxicological effects

Acute toxicity In high concentrations, vapors are anesthetic and may cause headache, fatigue, dizziness and

central nervous system effects. Harmful in contact with skin. Harmful if swallowed.

Components Species Test Results

Methylimidazole, 4- (CAS 822-36-6)

Acute Dermal

LD50 Rabbit 440 mg/kg

Phenol (CAS 108-95-2)

<u>Acute</u> Dermal

LD50 Rat 669 mg/kg

TRIETHYLENETETRAMINE (CAS 112-24-3)

Acute
Dermal
Liquid

LD50 Rat 1465 mg/kg

Oral *Liquid*

LD50 Rat 1716 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Methylimidazole, 4- (CAS 822-36-6) 2B Possibly carcinogenic to humans.

Phenol (CAS 108-95-2) 3 Not classifiable as to carcinogenicity to humans.

Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not applicable.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Phenol 1.46

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the Disposal instructions

material under controlled conditions in an approved incinerator. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel] Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN3259

UN proper shipping name Amines, solid, corrosive, n.o.s., or Polyamines, solid, corrosive n.o.s.

(TRIETHYLENETETRAMINE, Methylimidazole, 4-), Limited Quantity

Transport hazard class(es)

Class 8 Subsidiary risk Label(s) 8 Ш Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IB8, IP3, T1, TP33 Special provisions

Packaging exceptions 154 Packaging non bulk 213 Packaging bulk 240

IATA

UN3259 **UN number**

Amines, solid, corrosive, n.o.s. (TRIETHYLENETETRAMINE, Methylimidazole, 4-), Limited **UN proper shipping name**

Quantity

Transport hazard class(es)

8 Class Subsidiary risk Packing group Ш **Environmental hazards** Nο **ERG Code** 8L

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

UN3259 **UN number**

AMINES, SOLID, CORROSIVE, N.O.S. or POLYAMINES, SOLID, CORROSIVE, N.O.S. **UN proper shipping name**

(TRIETHYLENETETRAMINE, Methylimidazole, 4-), Limited Quantity

Transport hazard class(es)

8 Class Subsidiary risk Packing group Ш **Environmental hazards**


Marine pollutant No. F-A, S-B **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

DOT; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Phenol (CAS 108-95-2)

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Phenol (CAS 108-95-2) Listed.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Phenol (CAS 108-95-2) Listed.

SARA 304 Emergency release notification

PHENOL (CAS 108-95-2) 1000 LBS OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)	
Phenol	108-95-2	1000		500	10000	

SARA 311/312 Hazardous Yes

Classified hazard

chemical

Acute toxicity (any route of exposure)

Skin corrosion or irritation categories

Serious eye damage or eye irritation Respiratory or skin sensitization

Specific target organ toxicity (single or repeated exposure)

Material name: DEVCON® Titanium Putty Hardener 5318N Version #: 01 Issue date: 05-29-2019

SARA 313 (TRI reporting)

 Chemical name
 CAS number
 % by wt.

 Phenol
 108-95-2
 5 - 10

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Phenol (CAS 108-95-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Phenol (CAS 108-95-2) Low priority

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State

of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Methylimidazole, 4- (CAS 822-36-6) Listed: January 7, 2011 Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Glass Oxide (CAS 65997-17-3) Methylimidazole, 4- (CAS 822-36-6)

Phenol (CAS 108-95-2)

Titanium Dioxide (CAS 13463-67-7)

International Inventories

O-----

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 05-29-2019

Version # 01

HMIS® ratings Health: 3

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 3

Flammability: 1 Instability: 0

Material name: DEVCON® Titanium Putty Hardener 5318N Version #: 01 Issue date: 05-29-2019

Disclaimer

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.